

Example 6.38 (Bandpass filtering). Consider a LTI system with the impulse response

$$h(t) = \frac{2}{\pi} \text{sinc}(t) \cos(4t).$$

Using frequency-domain methods, find the response y of the system to the input

$$x(t) = -1 + 2 \cos(2t) + \cos(4t) - \cos(6t).$$

Solution. Taking the Fourier transform of x , we have

$$\begin{aligned} X(\omega) &= -2\pi\delta(\omega) + 2(\pi[\delta(\omega-2) + \delta(\omega+2)]) + \pi[\delta(\omega-4) + \delta(\omega+4)] - \pi[\delta(\omega-6) + \delta(\omega+6)] \\ &= -\pi\delta(\omega+6) + \pi\delta(\omega+4) + 2\pi\delta(\omega+2) - 2\pi\delta(\omega) + 2\pi\delta(\omega-2) + \pi\delta(\omega-4) - \pi\delta(\omega-6). \end{aligned}$$

The frequency spectrum X is shown in Figure 6.22(a). Now, we compute the frequency response H of the system.

Using the results of Example 6.36, we can determine H to be

$$\begin{aligned} H(\omega) &= \mathcal{F}\left\{\frac{2}{\pi} \text{sinc}(t) \cos(4t)\right\}(\omega) \\ &= \text{rect}\left(\frac{\omega-4}{2}\right) + \text{rect}\left(\frac{\omega+4}{2}\right) \\ &= \begin{cases} 1 & 3 \leq |\omega| \leq 5 \\ 0 & \text{otherwise.} \end{cases} \end{aligned}$$

from FT table:

$$1 \xleftrightarrow{\text{FT}} 2\pi\delta(\omega)$$

$$\cos(\omega_0 t) \xleftrightarrow{\text{FT}} \pi[\delta(\omega-\omega_0) + \delta(\omega+\omega_0)]$$

taking FT

Example 6.36 found the FT pair

$$\frac{2\omega_b}{\pi} \text{sinc}(\omega_b t) \cos(\omega_a t) \xleftrightarrow{\text{FT}} \text{rect}\left(\frac{\omega-\omega_a}{2\omega_b}\right) + \text{rect}\left(\frac{\omega+\omega_a}{2\omega_b}\right)$$

using result from Example 6.36 with $\omega_b = 1$, $\omega_a = 4$

definition of rect function

The frequency response H is shown in Figure 6.22(b). The frequency spectrum Y of the output is given by

$$\begin{aligned} Y(\omega) &= H(\omega)X(\omega) \\ &= \pi\delta(\omega+4) + \pi\delta(\omega-4). \end{aligned}$$

only two shifted delta functions are nonzero when $H(\omega) \neq 0$
[see Figures 6.22(a) and (b).]

Taking the inverse Fourier transform, we obtain

$$\begin{aligned} y(t) &= \mathcal{F}^{-1}\{\pi\delta(\omega+4) + \pi\delta(\omega-4)\}(t) \\ &= \mathcal{F}^{-1}\{\pi[\delta(\omega+4) + \delta(\omega-4)]\}(t) \\ &= \cos(4t). \end{aligned}$$

taking inverse FT

from table of FT pairs

$$\cos(\omega_0 t) \xleftrightarrow{\text{FT}} \pi[\delta(\omega-\omega_0) + \delta(\omega+\omega_0)]$$




Figure 6.22: Frequency spectra for bandpass filtering example. (a) Frequency spectrum of the input x . (b) Frequency response of the system. (c) Frequency spectrum of the output y .